

MATERIAL SAFETY DATA SHEET

5001-5008
5024-5056
5024 deleted

SPANTEX® (Fill-TEX, Roll-TEX, Color Coat)

June 1, 1996

SECTION I

Manufacturer's Name: Tex Enterprises, Inc.
1302 West Main St. Suite #13
Auburn, WA 98001

Emergency Telephone Number: (206)939-1660 Tex Enterprises, Inc.
1(800)535-5053 Infotrac, Inc. - Chemical Emergency Response System

Common Name: SPANTEX®

SECTION II HAZARDOUS INGREDIENTS

<u>Chemical and Common Name</u>	<u>%</u>	<u>Applicable Exposure Limits TLV/ACGIH</u>
Xylene	48	100ppm
Ethylene Glycol Monopropyl Ether	7	not established
Bisphenol A/Epichlorohydrin Based Epoxy Resin	2	not established

Volatile Organic Content, g/L = 628 (EPA Method 25, CFR Pt.60, App.A)

This product is a "Noncomplying Architectural Coating" in areas where VOC limits are in effect
Portland AQMA post July 1, 1996 manufactured date

Carcinogenic Ingredients

Substances present at a concentration of 0.1% or more classified as a carcinogen by IARC, NTP or OSHA: None

SECTION III HEALTH HAZARD DATA

Acute Health Effects

Inhalation: Headache and dizziness TLV - 100ppm
Ingestion: Burning sensation, nausea, and vomiting
Eyes: Irritant
Skin: Irritant

(Signs and Symptoms of Exposure) High vapor concentrations are anesthetic, irritating to the eyes and the respiratory tract, may cause headaches and dizziness and may have other central nervous system effects. Product contacting the eyes may cause eye irritation.

Chronic Health Effects

ASPIRATION INTO LUNGS DURING INGESTION MAY CAUSE MILD TO SEVERE PULMONARY INJURY AND POSSIBLY DEATH.

Prolonged or repeated skin contact with this product tends to remove skin oils possibly leading to irritation and dermatitis.

Emergency and First Aid Procedures

Inhalation: If overcome by vapor, remove to fresh air. If breathing is irregular or has stopped, start resuscitation, administer oxygen and call a physician immediately. Keep warm.
Ingestion: DO NOT INDUCE VOMITING, CALL A PHYSICIAN IMMEDIATELY.
Eye Contact: If splashed into the eyes, flush with water or suitable eye wash. If irritation persists, call a physician.
Skin Contact: If on skin, remove any contaminated clothing and wash skin thoroughly with soap and water.



980239B

SECTION IV CHEMICAL DATA

Boiling Point (degrees F)	280°-318°
Vapor Pressure (mm Hg.)	46
Vapor Density (Air=1)	3.66
Specific Gravity (H2O=1)	1.15
Percent Volatile by Volume (%)	58%
Evaporation Rate (But.Ace=1)	0.6
Solubility (Specify Solvents)	Neg.
Appearance and Odor	Paint in various colors-Aromatic

DATA SECTION V PHYSICAL HAZARD

Flash Point (Method Used)	84° F/30° C (TCC)
Extinguishing Media	Dry Chemical - Foam - CO2

Special Fire Fighting Procedures

Remove ignition source - Direct extinguisher at base of flame.

Use dry chemical, foam or carbon dioxide. Water may be ineffective, but water should be used to keep fire-exposed containers cool. Minimize breathing gases, vapor, fumes or decomposition products. Use supplied-air breathing equipment for enclosed or confined spaces or as otherwise needed.

The inclusion of the phrase "water may be ineffective" is to indicate that although water can be used to cool and protect exposed material, water may not extinguish the fire unless used under favorable conditions by experienced fire fighters trained in fighting all types of flammable liquid fires.

Incompatibility (Materials to avoid)

Strong oxidants such as liquid chlorine, concentrated oxygen, sodium hypochlorite or calcium hypochlorite.

Hazardous Decomposition Products

Carbon Monoxide if combustion incomplete, CO2, trace Sulphur Dioxide

Hazardous Polymerization: Will not occur

Stability: Stable Avoid heat or open flame

SECTION VI SPILL OR LEAK PROCEDURES

Steps to be taken in case Material is released or spilled

Remove any ignition sources

Add absorbent (e.g. Vermiculite) or dike to spill area to keep product out of sewers and watercourses. Advise authorities if product has entered or may enter sewers, watercourses, or extensive land areas.

Ventilate enclosed areas.

Waste Disposal Method

Our studies indicate that this product contains no regulated substances when it is solidified. To solidify, either leave can open and let it age to dry or to accelerate the drying process, spread out on plastic or cardboard and let dry. In this solid state it is permissible to dispose of in landfill. If in doubt, contact your local landfill or call Tex Enterprises, Inc. for a copy of the test results.

Assure conformity with applicable governmental regulations. Continue to observe precautions for volatile, flammable vapors from absorbed material.

SECTION VII EXPOSURE CONTROL INFORMATION

Respiratory Protection: Respirator for organic vapors, dusts, fumes and mists. Individuals who have problems with solvents may need to use a mask with supplied air.
Ventilation: Cross ventilate.
Protective Gloves: Chemical or solvent resistant.
Eye Protection: Safety glasses with side shields.

SECTION VIII SPECIAL PRECAUTIONS

Precautions to be Taken in Handling and Storing

USE EXPLOSION PROOF EQUIPMENT. NO SMOKING OR OPEN LIGHTS!!!!

Keep containers closed when not in use. Do not handle or store near heat, sparks, flame or strong oxidants.

Store in cool dry place

Maintenance Personnel

This product contains Sara 313 toxic chemicals:
CAS#1330-20-7
CAS#2807-30-9
CAS#25068-38-6

Shipping Personnel

Weight per gallon: 10 pounds

Department of Transportation Information:

D.O.T. Proper Shipping Name: Coating solution
D.O.T. Label Required: Flammable Liquid
D.O.T. Hazard Class or Division: 3
D.O.T. I.D. Number: UN1139
D.O.T. Packing Group III

Bill of Lading to read: Coating Solution,3,UN1139,PG III

NOTE: Boxes containing one gallon size pails qualify as a Ltd.Qty.
(see 49 Code of Regulations 173.150)

Limited Quantity exception is not for Aircraft transportation

When taking advantage of Limited Quantity exception - Bill of Lading reads: Coating Solution,3,UN1139,PG III, Ltd.Qty.

Coating solution is not listed in the Hazardous Substances nor Marine Pollutants tables in the 49 CFR

The information in the Material Safety Data Sheet is based on data of which we are aware and is believed to be correct as of the date hereof. Tex Enterprises, Inc. does not warrant or guarantee the accuracy or reliability of this information and shall not be liable for any loss or damage arising out of the use thereof. The information and recommendations are offered for the user's consideration and examination. It's the user's responsibility to satisfy himself of the uses of this product and if it is suitable for his particular purpose.

This revision of March 17,1996 MSDS is to include VOC rules
Prepared by - Sharon Waller